



The
Patent
Office

EK008796404U



INVESTOR IN PEOPLE

The Patent Office
Concept House
Cardiff Road
Newport
South Wales
NP10 8QQ

JC525 U.S. PRO
09/465946



I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated 21 October 1999

THIS PAGE BLANK (USPTO)

**Request for grant of a patent**

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

21DEC98 E413099-1 D02738
P01/7700 0.00 - 9827940.9 The Patent Office

Cardiff Road
Newport
Gwent NP9 1RH

1. Your reference

P-UK-CS1062#SP

2. Patent application number
(The Patent Office will fill in this part)

18 DEC 1998

9827940.9**3. Full name, address and postcode of the or of each applicant (underline all surnames)**

Black & Decker Inc.
Drummond Plaza Office Park
1423 Kirkwood Highway
Newark, Delaware
USA

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

Delaware, USA

341214001

4. Title of the invention

A POWER SAW

5. Name of your agent (if you have one)

Anthony Charles Dlugosz, Darrin Maurice Shaya.
Simon Harries, Ian Bell
Black & Decker
European Patent Department
210 Bath Road
Slough
Berks SL1 3YD
United Kingdom

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

Patents ADP number (if you know it)

7572555001

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number
(if you know it)Date of filing
(day / month / year)**7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application**

Number of earlier application

Date of filing
(day / month / year)**8. Is a statement of inventorship and of right to grant of a patent required in support of this request? (Answer 'Yes' if:**

Yes

- a) any applicant named in part 3 is not an inventor, or
 - b) there is an inventor who is not named as an applicant, or
 - c) any named applicant is a corporate body.
- See note (d))

Patents Form 1/77

9. Enter the number of sheets for any of the following items you are filing with this form. Do not count copies of the same document


Continuation sheets of this form	0
Description	14
Claim(s)	1
Abstract	1
Drawing(s)	9

10. If you are also filing any of the following, state how many against each item.

Priority documents	-
Translations of priority documents	-
Statement of inventorship and right to grant of a patent (Patents Form 7/77)	-
Request for preliminary examination and search (Patents Form 9/77)	1
Request for substantive examination (Patents Form 10/77)	-
Any other documents (please specify)	-

11.

I/We request the grant of a patent on the basis of this application

Signature  Date: 17 December 1998
DARRIN SHAYA

12. Name and daytime telephone number of person to contact in the United Kingdom

DARRIN SHAYA 01753 500804

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

A POWER SAW

The present invention relates to a power saw and has particular, although not exclusive, relevance to such a power saw which may be operated with a plurality of interchangeable saw blades.

Although the concept of using a power saw with a plurality of interchangeable blades has been known for many years, there is a tendency for the blades which are interchanged to be of the same physical size. The only significant difference between the blades tends to be the nature of the saw teeth. For example teeth of differing pitches are used when sawing wood as opposed to metal.

It has, however, been found that it would be useful if a power saw could accept a plurality of different saw blades of differing sizes as well as of differing natures. Such a provision could enable the power saw to operate in totally different sawing modes, depending upon which blades are used.

For example, if the power saw were able to accept a large woodsawing blade (such as are used for cutting tree branches or wooden logs) and also a small jigsaw blade, then a truly versatile saw would be available. The saw could then be readily adapted to different sawing modes by the user simply changing the blades.

Although the above aim is highly desirable, there exist certain difficulties. For example, a large power saw (so-called "panel saw") has fundamentally different characteristics to those of a jigsaw.

Panel saws tend to be large, heavy and bulky saws having high-powered motors. This is because in use of the saw, a large workpiece and a high amount of stock are worked upon. Also, a high degree of accuracy in the sawing process tends
5 not to be necessary.

By contrast jigsaws tend to be relatively small, lightweight saws with smaller, often variable-speed, motors. Because the workpiece on which a jigsaw is used is usually small
10 and/or thin, then smaller saw blades are used. Furthermore there is often the need for a high degree of accuracy when sawing with a jigsaw.

Additionally, the panel saw and jigsaw blades are usually
15 held at different angles relative to a workpiece. A panel saw blade is often brought down into contact with a workpiece generally parallel therewith, whilst a jigsaw blade cuts into a workpiece from the side.

20 The above differences mean that a jigsaw will need to have a sole plate in order to guide the saw blade during cutting and also to enable the user of the jigsaw to maintain the attitude of the blade constant with respect to the workpiece. A panel saw, however, often needs no such sole
25 plate.

It would thus be highly desirable for a saw capable of operating in a plurality of modes, such as a panel saw and a jigsaw, to have a sole plate when needed, but no sole plate
30 when not needed.

Accordingly the present invention provides a body and a motor housed within the body; the motor arranged to power a reciprocable shaft on which a blade for sawing may be
35 mounted; a pivotable sole plate attached to the body and

arranged to be held relative thereto in a plurality of positions such that in at least one position the sole plate acts as a guide for use of the power saw as a jigsaw with the blade for sawing passing through the sole plate in use of the power saw as a jigsaw. By allowing the sole plate to be pivotable into and out of a plurality of positions, then the above desirable advantages may be met.

Preferably the body of the power saw defines two working surfaces either of which may, during use of the power saw, abut a workpiece, and wherein the pivotable sole plate may be pivoted to rest against either of these two surfaces. If one of the working surfaces is used when the saw is in a panel saw mode, then the sole plate may abut the other during use. Conversely, if the other working surface is used when the saw is in a jigsaw mode, the sole plate may abut the said one working surface. The pivotable sole plate may be lockable in any one of the plurality of positions.

In a preferred embodiment the body is shaped to define a recess within which the pivotable sole plate may sit when in at least one of the plurality of positions. This permits the sole plate to be kept out of the way of the user when desired during certain sawing operations. Also, the sole plate may include visual indicia to act as a guide to align the power saw with a workpiece.

The present invention will now be described, by way of example only, and with reference to the accompanying drawings, of which:-

Figure 1 shows a reciprocable shaft on which a saw blade may be mounted in accordance with an embodiment of the present invention;

Figure 2 shows the shaft of Figure 1, but with a saw blade mounted thereon in an operating position from one side; Figure 3 shows the view of Figure 2, but from the other side of the saw blade;

5

Figure 4 shows a side view of the reciprocable shaft of Figure 1, but with the retaining member thereof being in an unlocked position;

10 Figure 5 shows the shaft of Figure 1 with the saw blade mounted thereon in a locked position;

Figure 6 shows a sectional view along the line A-A of Figure 5;

15

Figure 7 shows a sectional view along the line B-B of Figure 5;

20 Figure 8 shows a side view of a saw blade and the reciprocable shaft of Figures 2 and 3 in an unlocked position;

Figure 9 shows the view of Figure 8, but with the saw blade now retained in its stored and locked position;

25

Figure 10 shows a schematic illustration of the motor and internal mechanisms of a power tool in accordance with an embodiment of the present invention;

30 Figure 11 shows a schematic side representation of Figure 10;

Figure 12 shows a side view of a powered saw in accordance with an embodiment of the present invention; and

35

Figure 13 shows a side view of an alternative use of a powered saw to that of Figure 12.

Referring firstly to Figure 1, there is shown a shaft (2) formed from pressed metal, such as steel, and having in the centre thereof a yoke (4). One end of the shaft (2) is formed integrally with a depending retaining member, here a blade mount (6). The blade mount (6) comprises a restraining means, here two arms (8) which depend from the shaft (2). The blade mount further includes a pin (10) which will be described in more detail below.

Referring now also to Figures 2 and 3, it can be seen that the shaft (2) is arranged to drive a saw blade (12) presented thereto and which is mounted on the blade mount (6). It can be seen that the saw blade (12) has a shank (14) which has formed therein a hole (16) (see more clearly Figures 5, 8 and 9) for mounting the blade (12) on a lug (18) of the pin (10).

Referring now to Figure 4, it can be seen that the pin (10) comprises a head (20) formed on one side of the blade mount (6) and a lug (18) co-operating with the head (20) formed on the other side of the blade mount (6). The shape of the lug (18) is the same as that of the hole (16) formed in the blade (12). This allows for the blade (12) to be mounted snugly on the lug (18).

The pin (10) is rotatable about its axis shown as X-X in Figure 4 and it can be seen from this figure that the blade mount (6) has a recess (21) formed therein such that the lug (18) may sit within the recess (21) when it is in one of two positions. Because the pin (10) is rotatable about the axis X-X, then whenever the lug (18) is aligned with the recess (21) (in either of two positions 180° apart) then it will

fit within the recess (21). In any other position, the lug (18) cannot sit within the recess (21).

5 In order for the lug (18) to be selectively aligned or not with the recess (21), the head (20) of the pin (10) is spring biased. In this manner, therefore, whenever the lug (18) is aligned with the recess (21) it "pops" into the recess and is held therein until the user exerts sufficient force against the head (20) against the action of the spring
10 (described later below) to force the lug (18) out of the recess (21) and therefore allow the pin (10) to be rotated about the axis X-X.

Referring now additionally to Figure 5, it can be seen that
15 the saw blade (12) is held in its locked position (because the lug (18) is within the recess (21)) against the shaft (2). Because the shaft (2) is arranged to reciprocate, that is drive the blade (12) backwards and forwards along a linear path, then it will be understood that each of the
20 arms (8) is arranged to flank the shank (14) of the blade (12) to prevent the blade (12) from becoming detached from the blade mount (6). This is because the arms (8) prevent any movement of the blade (12) in a direction perpendicular to the direction of reciprocation of the shaft (2).

25

In order to understand the operation of the pin (10) and its interaction with the blade (12), reference will now be made in particular to Figures 5, 6 and 7.

30 The pin (10) is spring biased, and in the case of Figure 6, it can be seen that the head (20) of the pin (10) has not been depressed and therefore under the action of the spring (22), the head (20) is forced to the left of Figure 6 therefore allowing the lug (18) to sit within the recess
35 (21). This does, of course, presuppose that the lug (18) is

aligned with the recess (21) as has been described here
above. Assuming this to be the case, then the blade will be
locked in this position. Rotation of the pin and therefore
the lug (18) are not possible because the lug (18) is
5 located within the housing (20).

Referring now to Figure 7, it will be described how the lug
(18) is released from the recess (21) in order to allow
rotation of the saw blade (12).

10

In Figure 7 the user has pushed the head (20) to the right
of the figure and therefore caused compression of the spring
(22). The movement of the pin (10) to the right of the
figure releases the lug (18) from the recess (21) and
15 therefore allows rotation of the pin (10) about its axis
X-X. Because the lug (18) is now no longer located within
the recess (21) then rotation of the pin (10) means that the
blade (12) may be rotated as well. Referring also to Figure
8, this shows how the saw blade (12) has been rotated
20 through 90° as compared with the locked position of Figure
5.

Whilst referring to Figure 8, it can be seen that, because
the blade (12) is now perpendicular to the shaft (2) rather
25 than parallel therewith as was the case in Figure 5, then
the shank (14) of the saw blade (12) is no longer
constrained by the arms (8) of the blade mount (6). This
means that the entire blade (12) may be removed from the lug
(18) and could, for example, be replaced by an alternative
30 saw blade.

Referring now to Figure 9, it can be seen that further
rotation of the pin (10) and the blade (12) is possible
(because there is no alignment between the lug (18) and the
35 recess (20)). The saw blade (12) as shown in Figure 9 has

now been rotated through 180° with respect to that of Figure 5. It will be appreciated that the lug (18) is now re-aligned with the recess (21) and therefore if the user ceases to apply any force to the head (20) of the pin (10),
5 then the lug (18) may fall back into the recess (21) and therefore lock the saw blade (12) in the position shown. This may be useful when the saw is to be carried around but the blade needs to be kept safely within the body of the saw, for example, to avoid injuring a user or damage to the
10 saw blade.

Although only shown in dotted outline in Figure 9, it will be understood that a further pair of arms (8) may be employed in the blade mount (6) to retain the saw blade (12) in the
15 position shown.

Referring now to Figures 10 and 11 particularly, the internal mechanism of the power tool embodying the present invention will be described. In these examples, the power
20 tool is a power saw.

An electric motor (24) is operable in conventional manner to drive a motor spindle (26) coupled to a drive wheel (28). The teeth of the drive wheel (28) mesh with the teeth of a
25 gear wheel (30) having formed thereon an eccentric (32). Although not shown in the drawings, the eccentric (32) must be counter-balanced and those skilled in the art will appreciate this fact.

30 The eccentric (32) fits into the yoke (4). In this way, when the motor (24) is activated, it drives the drive wheel (28) which in turn causes rotation of the gear wheel (30). The circular movement of the eccentric (32) sitting in the yoke (4) therefore causes a linear reciprocal motion of the
35 shaft (2) in a right-left-right motion as the drawings are

viewed. In order to ensure that the only motion of the shaft (2) at the operative end (that is where the blade (12) and the blade mount (6) are situated) occurs, a retaining bar (34) having linear bearings surrounds the shaft (2).

5 This restrains movement of the shaft only in the left-right-left linear direction.

Whilst in the above examples of Figures 10 and 11 only one drive wheel (28) is shown, those skilled in the art will appreciate that any desired gearing arrangement may be used. The choice of gearing arrangement will depend primarily on the step up/step down requirement between the rotational output speed of the motor (24) and the frequency of linear reciprocation needed for the shaft (2).

15

Referring now particularly to Figures 12 and 13, two further embodiments of the present invention are now described. It can be seen by comparing these two figures, that the power tools shown therein share the same body (36). However, the tools shown in Figures 12 and 13 each are used for a different purpose and operate in different modes, as will be described here below. It should be understood that, for the purposes of Figures 12 and 13, the internal mechanism as shown in Figures 10 and 11 is incorporated therein.

20 However, because Figures 12 and 13 show the tool from the outside, then the internal mechanisms cannot be seen.

In Figure 12, the tool is used as a so-called panel saw. Panel saws are generally used for sawing large pieces of wood and the like in the form of blocks such as logs. In the present invention, it has been found desirable to be able to offer the user the facility of using the panel saw not only in its powered mode but also manually. That is, the user should be able to grip the handle (38) of the panel saw and use it as a conventional manually operated saw

30

35

whether the blade is being driven by the motor (24) or not. To achieve this the saw needs to be lightweight but also it has been found that, when the saw is being driven by the motor (24), conventional reciprocating action will prevent manually using the tool with ease, because of the combination of the frequency of reciprocation of the saw blade (12) and the length of each reciprocal stroke.

Conventionally, it has been found that the frequency of reciprocation of the blade (12) has been around 3,000 strokes per minute. Additionally, the length of each reciprocal stroke has been in the region of 20mm. The combination of this particular frequency and stroke length results in large vibrational forces being felt by the user. Additionally, this creates large internal forces which also need to be overcome in order to be able to use the saw manually. With a conventional panel saw, therefore, if the user wishes to use it manually rather than in its conventional powered mode, a degree of discomfort would be felt because the saw would be vibrating at a frequency which does not lend itself to holding the saw comfortably. Additionally, the amplitude of each reciprocal stroke of the blade (12) is so large that high inertial forces are felt by the user mean that to be able to pull and push the saw in a manual mode is not easily achievable.

It has been found that by reducing the length of each reciprocal stroke to preferably around 10mm and concomitantly increasing the reciprocal stroke frequency to preferably around 6,500 strokes per minute, that this combination of lower stroke length and higher frequency results in less adverse vibrational and inertial forces being felt by the user. This then enables the panel saw of Figure 12 to be used as a manual saw simply by holding the handle (38). Additionally, if the user requires a further

grip on the body (36), a recess, formed as insert (40) is available for gripping by the other hand of the user (that is the hand which does not grip the handle (38)).

5 Although in the example described with reference to Figure 12 the preferred frequency of oscillation has been given as 6,500 strokes per minute, the present invention has been found to operate effectively with a frequency of vibration
10 between 3,000 and 10,000 strokes per minute. Similarly, although the preferred amplitude of each reciprocal stroke is given as 10mm, it has been found that the present invention works effectively with a range of 5 to 15mm.

Referring now also to Figure 13, it can be seen that the
15 same body (36) is used with a different saw blade (12). Indeed, the saw blade (12) is that found on conventional "jigsaws". Jigsaws are tools which are used with relatively small saw blades and are used for cutting accurate shapes in a workpiece. Conventionally, jigsaws are
20 held relative to the workpiece in a different attitude to panel saws. This can be seen by reference to the difference in attitude between Figure 12 and 13. In Figure 13, the body (36) can be seen resting on a block (42) which represents a workpiece. In use of the jigsaw, the body (36)
25 would be held on the block (42) in the attitude shown in Figure 13.

It can be seen from Figure 13 that the handle (38) is now positioned relative to the workpiece (42) such that the body
30 (36) may easily be used as a jigsaw. In use of the jigsaw, a user exerts a force via the handle (38) in the direction of the large arrow marked "A". This is so that the blade (12) is driven also in the direction of the arrow "A" to cut through the workpiece.

35

It can be seen by comparing Figures 12 and 13, that the handle (38), although itself the same in both figures, it able to be used for exerting forces in a different direction depending on which mode of use (either the panel saw of
5 Figure 12 or the jigsaw of Figure 13) the tools are put to.

The handle (38) is positioned adjacent a trigger (44) which trigger (44) is operable by user when the handle (38) is gripped.

10

It can be seen from both Figures 12 and 13, therefore, that the position of the handle (38) relative to the body (36) is such that the user may operate the saw in a plurality of positions relative to a workpiece. Thus, regardless of
15 whether the tool is being used as a panel saw in Figure 12 or a jigsaw in Figure 13, the same handle is used for operating the saw. It will be appreciated by those skilled in the art, that this holds true whether the panel saw of Figure 12 is being used as a powered saw by powering the
20 motor (24) via an electricity supply cable (46), or whether it is being used manually.

In the examples shown, the trigger (44) is formed integrally with the handle (38). This need not necessarily be the
25 case, and the trigger may be formed separately or indeed on another part of the body (36).

From Figures 12 and 13, therefore, it can be seen that the handle (38) is accessible from one of two sides, depending
30 on whether the tool is to be used as a panel saw or a jigsaw. It is envisaged that the present invention is of scope to allow more than two sides of the handle (38) to be used depending on the purpose to which the tool is being put.

35

It can be seen from Figures 12 and 13, that the body (36) also includes a pivotable sole plate (48). The sole plate (48) is pivotable about pivot point (50). The pivot point (50) includes a means (not shown) for allowing the sole plate (48) to be held at any one of a desired position around the range of possible pivotable positions about the point (50). In the example of Figure 12, the sole plate (48) is tucked underneath the body (36). In the example of Figure 13, the sole plate (48) is pivoted through 270° so as to act as the guide sole plate for a conventional jigsaw. In this mode, the blade (12) passes through the sole plate (48) when used in its jigsaw mode.

Those skilled in the art will appreciate that, conventionally, jigsaws use a sole plate (48) to act as a guide when cutting a workpiece. In the example of Figure 13, although it cannot be seen from the drawing, the sole plate (48) includes visual indicia to allow the user to see exactly where the blade (12) will cut the workpiece when viewed from above the body (36).

It can be seen by comparing Figures 12 and 13, therefore, that the body (36) defines two working surfaces (52 and 54) dependent upon which mode the tool is being used. In the examples above, working surface (52) is used for the jigsaw mode of Figure 13 and working surface (54) is used for the panel saw mode of Figure 12.

It will be understood by those skilled in the art that the sole plate (48) may be positioned at any suitable angle relevant to the body (36) dependent upon the use to which the tool is being put.

By referring now particularly to Figure 13 it can be seen that, when the tool is used as a jigsaw, a user may also grip the dimpled surface (56) in order to assist with

guiding the tool during use. Alternatively, this surface (56) can be used to form cooling vents within the body of the saw.

CLAIMS




1. A power saw including: a body and a motor housed within the body; the motor arranged to power a reciprocable shaft
5 on which a blade for sawing may be mounted; a pivotable sole plate attached to the body and arranged to be held relative thereto in a plurality of positions such that in at least one position the sole plate acts as a guide for use of the power saw as a jigsaw with the blade for sawing passing
10 through the sole plate in use of the power saw as a jigsaw.
2. A power saw according to claim 1, wherein the body of the power saw defines two working surfaces either of which may, during use of the power saw, abut a workpiece, and
15 wherein the pivotable sole plate may be pivoted to rest against either of these two surfaces.
3. A power saw according to either claim 1 or claim 2 wherein the pivotable sole plate is lockable in any one of
20 the plurality of positions.
4. A power saw according to any one of the preceding claims, wherein the body is shaped to define a recess within which the pivotable sole plate may sit when in at least one
25 of the plurality of positions.
5. A power saw according to any one of the preceding claims, wherein the pivotable sole plate includes visual indicia to act as a guide to align the power saw with a
30 workpiece.
6. A power saw substantially as hereinbefore described and with reference to the accompanying drawings.

ABSTRACT


A POWER SAW

5 A power saw includes a body (36) housing a motor (24). The
motor drives a reciprocal shaft (2) on which a blade (12) is
mounted. The body is coupled to a pivotable sole plate
(48,50) which is held relative to the body (36) in a
plurality of positions such that in at least one position
10 the sole plate may act as a guide for use of the tool as a
jigsaw.



THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)



THIS PAGE BLANK (USPTO)

FIG 6

THIS PAGE BLANK (USPTO)




FIG 7




FIG 8

THIS PAGE BLANK





FIG 9

THIS PAGE BLANK

FIG 10

THIS PAGE BLANK 100




FIG 11

THIS PAGE BLANK (USPTO)




FIG 12

THIS PAGE BLANK (USPTO)

9/9




FIG 13

THIS PAGE BLANK (SEE 12)